

FOR CONSTRUCTION

# Multiple Treatment Rooms Linear Accelerators

## 6/10 MV Energy

---

## SAMPLE PROJECT

CONFIDENTIALITY NOTICE: This message and any attachments contain confidential and proprietary information and are solely for the intended recipient. If you are not the intended recipient, any disclosure, copying, use, or distribution of the information included in this message and any attachments is strictly prohibited. If you have received this communication in error, please notify us by reply e-mail and immediately and permanently delete this message and any attachments. Thank you for your understanding.

CONDITIONS OF USE: Attached files are for use in preparing planning, presentation, shop drawings or related project specific material. Data in attached files is part of VERITAS' s instruments of service and shall not be used, in whole or in part, by you or anyone else receiving this data through you or from you for any purpose other than preparing planning, presentation, shop drawings or related project specific material without express written consent from VERITAS. No sourcing, fabrication, installation, or construction is to be performed from ullached files. Allached files are not conitracd documenitls. Differences may exisl betweenl allached files and corresponding hurd copy documenitls. VERITAS makes rio represenitlalion regarding accuracy or completeness of attached files transmitted herein.

WHEN THIS DOCUMENT IS SUPPLIED TO EITHER OWNER OR CONTRACTOR, IN EITHER PAPER OR ELECTRONIC FORM, THE SUBSEQUENT USE OF THE INFORMATION CONTAINED ON THE DOCUMENT IS SUBJECT TO THE CONDITIONS OF THE AGREEMENT BETWEEN THE OWNER AND VERITAS AND TO VERITAS' COPYRIGHT AND OTHER SUCH RIGHTS IN THIS DOCUMENT. CONTRACTOR MAY MAKE ELECTRONIC FILES OF THIS DOCUMENT AVAILABLE TO SUBCONTRACTORS, SUBJECT TO THIS STATEMENT OF CONDITIONS OF USE! SOLELY AS A CONVENIENCE TO SUCH SUBCONTRACTORS IN THEIR PREPARATION OF SHOP DRAWINGS. THE PROVISION OF THIS DOCUMENT BY VERITAS SHALL NOT MAKE VERITAS RESPONSIBLE IN ANY WAY FOR ANY ASPECT OF THE SUBCONTRACTOR'S SHOP DRAWINGS, NOR RELIEVE SUBCONTRACTORS FROM FULL RESPONSIBILITY FOR PREPARATION OF THEIR REQUIRED SHOP DRAWINGS.



1

2

3

4

5

6

7

8

A

B

C

D

E

F

G

H

Notes for Construction

1. Physics and design layout is that of Veritas Medical Solutions, LLC. Project scope and associated drawings are based on these (approved) documents.

2. All demolition, site preparation work etc, must be complete prior to installation shielding or finish materials by Veritas Medical Solutions, LLC. Coordination with project construction staff and a Veritas representative is required to ensure field conditions are appropriate as called for in the Veritas quotation.

3. If VeriShield™ materials are to be installed against an existing structure it is the general contractor's responsibility to ensure that existing surfaces, including floors and ceilings are free of all protrusions, debris bumps, etc. Surface is to be flat, plumb and level within 1/2" (6.35mm) in all directions.

4. Project construction staff is required to provide adequate access to the site in accordance with Veritas quotation and contract conditions. Additionally, proper protection is required for equipment, including but not limited to interior storage for electronics, doors, frames, drives, etc.

5. Shielding thickness as indicated on drawings is nominal. Veritas Medical Solutions, LLC provides a shielding guarantee,therefore variations in nominal thickness will not compromise shielding. Approval of any shielding changes is to be approved by Veritas Medical Solutions, LLC.

6. Veritas Medical Solutions, LLC reserves the right to make any changes in layout, shielding, or design, in order to ensure shielding integrity to the project and provide more practical means of installation. Any field changes approved by Veritas will be incorporated into a final As Built set of drawings.

7. Any contemplated penetrations through shielded barriers regardless of how small and how few are to be coordinated through Veritas Medical Solutions. Veritas proposal outlines approved penetrations for HVAC, electrical, dosimetry pipes, etc.

8. All structural steel to be equivalent to ASTM A-992, Grade 50 or ASTM A-36 as noted on structural plans. All structural tubing to be equivalent to ASTM 500 Grade B.

9. All steel that will ultimately be exposed to weather is to be factory painted with rust inhibitive based primer.

10. All welds are to be properly prepared and ground smooth according to AISC standards.

11. Testing: Testing procedures to be as per Shielding Techniques for Radiation Oncology Facilities, McGinley, Medical Physics Publishing ©2002 (Second Edition)

12. Testing shall be performed in the presence of a Veritas representative. This will allow any potential modifications to be made in the most efficient and time effective manner.

13. Final shielding must be approved by an independent, qualified health physicist or expert in the field of radiation protection. These individuals are to be selected and employed by the client.

I. Pre- Installation and Site Preparation Instructions

A. Inspect the proposed installation area and confirm that preparations to the site have been accomplished by the general contractor (foundations, any required demolition, protection of existing conditions, provision of proper access routes, etc.) prior to the installation commencement of VeriShield™ materials.

B. Provide proper access routes to the installation area. Proper coordination between trades must be established in order to transport VeriShield materials to the installation site.

C. Provide adequate storage / staging area. Storage of materials will be in this defined area, which should be close to the installation area. NOTE: Any materials such as electronics, doors, frames, hardware, etc., must have adequate interior storage areas.

D. All utilities (water, electric, etc.) to be located in close proximity to the installation area.

II. Layout

E. VeriShield materials shall be installed from the most recent set of approved drawings. Upon layout of shielding, if any discrepancies are discovered on site, conditions should be resolved before commencing with installation.

F. First layer of VeriShield block shall be laid out (dry) around the entire perimeter of the proposed shielded structure. All accessory items, (door frames, lintels, dosimetry pipes, conduits, etc.) to be located at this time. Iso-center and column lines to be established and referred to during installation. Location of reinforced vertical and horizontal structural cells is to be identified at this time. Vertical rebar shall be anchored though floor slab at corners, intersections, typical.

III. Installation

G. Once VeriShield materials have been properly located, continue by placing first course of VeriShield™ in a bed of standard mortar. Mix mortar according to ASTM C270 specification. (2) Two horizontal structural cells are to be filled with VeriShield grouting material along with rebar embedded as indicated on structural drawings and details.

H. ShieldTech™ frames and drive assembly recess shall be set at door opening as called for in drawings. All frames are to be set plumb and square. Drive assembly recess is to be set according to specifications on door drive drawing.

Installation Notes:

1. A meeting with a Veritas Medical Solutions representative and the General Construction Group is required prior to the installation of VeriShield block. This meeting is intended to compare , inspect work of other trades that may affect successful installation of VeriShield™ block.

2. Before commencing with installation of VeriShield block, follow Pre-Installation Site Preparation Instructions Listed in drawing set.

3. Installation: First course of VeriShield block to be placed plumb, level and true to line in a bed of standard mortar.

4. Place all VeriShield block in a modified running bond pattern as called for on drawings and details herein. First (2) two courses of VeriShield block are placed in a "stack" bond. The (3rd) third course of block is offset to form a standard running bond pattern. The (4th) fourth course resumes stack bond. Subsequent courses of VeriShield block continue this (4) four course bond pattern accordingly.

5. Ensure all VeriShield block is installed with leveling bed of mortar at every (5th) fifth course of block. Maximum thickness of leveling bed is to be 1/2 inch. Placement of appropriate brick ties or mesh is to be adhered to as called for in the drawings and details. Note: For seismic conditions see structural drawings for further clarification.

6. It is only necessary to provide horizontal (bed) joints. Vertical (head) joints are not necessary. Ensure there are no voids. Lay all VeriShield units plumb, level and true to line in the modified bond pattern as described in item 4 above, as well as indicated on drawings. Note: For seismic conditions see structural drawings for further clarification.

7. If any VeriShield units are displaced after mortar has stiffened - Remove and replace unit following steps 3 - 6 above.

8. Strike flush all joints. Ensure the curved interlock is fully intact with adjacent VeriShield block.

9. Mortar used between VeriShield™ block shall be freshly mixed and shall be proportioned with 1 part portland cement, 1 part lime and 6 parts sand (Type S Mix). Mortar shall comply with ASTM C270 specification for Type S Mix.

10. Use all mortar within 2-1/2 hours after mixing.

11. Ensure all VeriShield™ block are installed in a professional manner and to the highest quality standards, according to drawings.

MATERIAL LEGEND

IN SECTION &/OR PLAN

EXISTING CONSTRUCTION

CONCRETE

CMU

VERISHIELD V230

VERISHIELD V250

VERISHIELD V300

LEAD (Pb) BRICK

LEAD (Pb) SHEET/PLATE

STEEL (Fe) SHEET/PLATE

HDPE SHEET/PLATE

HDPE BORATED SHEET/PLATE

ALUMINUM

PLYWOOD or:

GROUT (SHIELDED)

MORTAR

RIGID INSULATION

MODULAR SHIELDING LEGEND

IN SECTION and/or PLAN

1

NUMBER OF WYTHES - LOW DENSITY

1

no

NUMBER OF WYTHES - HIGH DENSITY

1

no

NUMBER OF THICKNESS (Inches) - LEAD

POINT LOAD - LOADING PLAN

GENERAL SCALE NOTE

SCALE NOTE: THE SCALE OF THESE DRAWINGS ARE APPROXIMATE. ALL EXISTING INTERIOR AND EXTERIOR WALLS, OPENINGS, ETC. ARE REPRODUCTIONS OF FIELD MEASUREMENTS AND OBSERVED EXISTING CONDITIONS. FIELD VERIFY ALL CONDITIONS PRIOR TO THE COMMENCEMENT OF CONSTRUCTION AND CONSULT ARCHITECT REGARDING ANY UNIDENTIFIED CONDITIONS.

MASONRY GROWTH NOTE

ALL DIMENSIONS AND MASONRY WYTHES INDICATED HEREIN ARE TO BE UNDERSTOOD AS NOMINAL DIMENSIONS ONLY. UNLESS OTHERWISE NOTED, DURING INSTALLATION, IT IS TO BE EXPECTED THE DIMENSION OF EACH WYTHE OF MASONRY TO INCREASE BY 1/8" PER COURSE REFLECTING ACTUAL WORKING CONDITIONS, IRREGULARITIES IN SHAPE OF BLOCK, AND CONSTRUCTION TOLERANCES, ETC. GROWTH IS TO BE ACCOUNTED FOR DURING LAYOUT IN THE FIELD PRIOR TO INSTALLATION.

veritas  
Medical Solutions

CONDITION OF USE

Issue Description: This drawing is for informational purposes only. It is not to be used for construction or other purposes without the express written consent of Veritas Medical Solutions, LLC. The user of this drawing is responsible for ensuring that the information contained herein is accurate and up-to-date. Veritas Medical Solutions, LLC is not responsible for any errors or omissions in this drawing. The user of this drawing is responsible for ensuring that the information contained herein is accurate and up-to-date. Veritas Medical Solutions, LLC is not responsible for any errors or omissions in this drawing.

REV. CONSTR. ISSUE

CONSTRUCTION ISSUE

REVISED ISSUE

REVIEW ISSUE

DRAWING ISSUE

DRAWN BY: RDA

CHECKED BY: MA

PROJECT NO: SCALE

AS NOTED


DRAWING TITLE

NOTES, LEGENDS, KEYPLAN

DRAWING NUMBER

XG-002


FOR CONSTRUCTION






DRAWING NUMBER  
**X-101**

FOR CONSTRUCTION




**B1** SECTION VIEW  
1:50  
CEILING SHIELDING

**B4** NOT USED  
1:50



**D1** SECTION VIEW THROUGH PRIMARY  
1:50  
CEILING SHIELDING



**H1 FLOOR PLAN**  
1:50  
CEILING SHIELDING

DRAWING NUMBER

**X-102**

SEAL

# SAMPLE PROJECT

## MULTIPLE TREATMENT ROOMS

### LINEAR ACCELERATORS

**veritas**  
Medical Solutions

## CONDITION OF USE

WHEN THIS DOCUMENT IS SUPPLIED TO EITHER OWNER OR CONTRACTOR, IN EITHER PAPER OR ELECTRONIC FORM, THE SUBSCRIBER AGREES THAT THE INFORMATION CONTAINED ON THE DOCUMENT IS SUBJECT TO THE CONDITIONS OF THE AGREEMENT BETWEEN THE OWNER AND VERITAS AND TO VERIFYING, COPYING AND OTHER SUCH RIGHTS IN THIS DOCUMENT. CONTRACTOR MAY MAKE ELECTRONIC FILES OF THIS DOCUMENT AVAILABLE TO SUBCONTRACTORS, SUBJECT TO THIS STATEMENT OF CONDITIONS OF USE, SOLELY AS A CONVENIENCE TO SUCH SUBCONTRACTORS IN THEIR PREPARATION OF SUCH DRAWINGS. THE PROVISION OF THIS DOCUMENT BY VERITAS SHALL NOT MAKE VERITAS RESPONSIBLE IN ANY MANNER FOR ANY ACTIONS OF THE SUBCONTRACTORS SUCH DRAWINGS. NOR SHALL VERITAS SUBCONTRACTORS FROM ALL RESPONSIBILITY FOR PREPARATION OF THEIR REQUIRED SUCH DRAWINGS.

	REV. CONSTR. ISSUE
--	--------------------

*		CONSTRUCTION ISSUE
*		REVISED ISSUE
*		REVIEW ISSUE

DRAWING ISSUE

DRAWN BY	CHECKED BY
----------	------------

RDA	MA
PROJECT NO	SCALE

PROJECT NO.	DATE
.	AS NOTED

★

DRAWING TITLE

DRAWING TITLE

CEILING

## SHIELDING

SHIELDING

1000

DRAWING NUMBER

Y 102

A-102

3

FOR CONSTRUCTION



1

2

3

4

5

6

7

8

A

B

C


D

E


F

G


H




B1 DETAIL

1:20  
WALL ELEVATION WITH STACKED BOND


B3 DETAIL

1:20  
WALL ELEVATION WITH RUNNING BOND


B5 DETAIL

1:20  
WALL SECTION WITH OFFSET BOND


B7 DETAIL

1:20  
WALL SECTION WITH IN-LINE BOND


E1 DETAIL

1:20  
BEARING PLATE - STRUCTURAL CELL


E3 DETAIL

1:20  
LASER MOUNTING PLATE


E5 DETAIL

1:20  
PIPE PENETRATION - FIBERCOAT


E7 DETAIL

1:20  
DOSIMETRY PIPE PENETRATION

H1 DETAIL

N.T.S.  
TYPICAL BLOCK

H3 DETAIL

1:10  
WALL TIES

H5 DETAIL

1:10  
HEADER BEAM

CORNERS OF MASONRY:  
FORM ALL CORNERS AND GROUT SOLID TO  
PROVIDE 90° ANGLES. ALL SURFACES TO  
BE SMOOTH, FLUSH AND PLUMB

DRAWING NUMBER  
X-500

SEAL

GENERAL NOTES

SCALE NOTE: THE SCALE OF THIS DRAWING IS APPROXIMATE. ALL EXISTING INTERIOR AND EXTERIOR WALLS, OPENINGS ETC. ARE REPRODUCTIONS OF FIELD MEASUREMENTS AND OBSERVED EXISTING CONDITIONS. FIELD VERIFY ALL CONDITIONS PRIOR TO THE COMMENCEMENT OF CONSTRUCTION AND CONSULT ARCHITECT REGARDING ANY UNIDENTIFIED CONDITIONS.

SAMPLE PROJECT  
MULTIPLE TREATMENT ROOMS  
LINEAR ACCELERATORS

veritas  
Medical Solutions

CONDITION OF USE

Veritas Medical Solutions warrants that the information contained in this document is accurate and complete as of the date of publication. Veritas Medical Solutions does not warrant the accuracy or completeness of the information contained in this document for any other purpose. Veritas Medical Solutions is not responsible for any errors or omissions in this document. Veritas Medical Solutions is not responsible for any damages, including consequential damages, arising from the use of this document. Veritas Medical Solutions is not responsible for any damages, including consequential damages, arising from the use of this document. Veritas Medical Solutions is not responsible for any damages, including consequential damages, arising from the use of this document.

REV. CONSTR. ISSUE

CONSTRUCTION ISSUE

REVISED ISSUE

REVIEW ISSUE

DRAWING ISSUE

DRAWN BY RDA

CHECKED BY MA

PROJECT NO. SCALE

AS NOTED

SHEET LABEL

DRAWING TITLE

DETAILS

DRAWING NUMBER

X-500

FOR CONSTRUCTION